



Designed to meet SIL1 requirements, the new MX 32 gas detection controller is an analog and digital controller that continuously measures and controls gases in the atmosphere. It uses the same platform as the MX 43 which has already proven to be a very high performing and reliable controller.

The new MX 32 manages both digital lines and analog channels and covers all needs for a wide variety of gas monitoring applications. Its digital technology allows up to eight detectors to be distributed on two lines for increased savings. The unit allows two inputs for Wheatstone bridge sensors.

Features & benefits

- One or two channels, up to four or eight detectors
- Manages both digital lines and analog channels and covers all needs for a wide variety of applications
- Manages Wheatstone bridge sensor inputs without the need of additional module
- Five programmable events per detector (one to three alarms, underscale, overscale) and fault event
- Two extra MOSFET outputs for driving the audible and visual alarms
- Front panel LEDs allow for a quick and basic overview of the installation and onboard alarm buzzer
- Easy to read large graphic and multi-language LCD back-lit display
- Up to eight detectors to be distributed on two lines for increased savings
- Smart keys make embedded menus easy to use

Applications

- Boiler room
- Food industry
- HVAC
- Automotive plants
- Steel mills
- Waste water treatment
- Petrochemical
- Laboratories

Approvals

- EMC, according to EN 50270:15
- SIL1 capability according to EN 50271:10 (pending)
- cCSAus approved for ordinary location

AMERICAS - Texas (USA)
4055 Technology Forest Blvd.
The Woodlands, TX 77381
Tel.: +1-800-247-7257
Fax: +1-281-292-2860

EMEA
ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

ASIA PACIFIC
290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365



Copyright © 2018 3M, 3M Gas & Flame Detection. All rights reserved.
gasdetection.3m.com. GF-00227B-EN

