



Gas & Flame Detection

3M™ Detcon™ CXT Wireless

Infrared LEL Gas Detection Sensor

Economical wireless gas detection

The CXT Wireless® gas detection sensors are easily and economically deployable in both permanent and temporary installations. This low power sensor assembly utilizes infrared technology for combustible hydrocarbons. All component parts are rated for Class 1; Division 1, Groups C, D hazardous areas. This advanced field device consists of a Model CXT low power infrared gas detection sensor, and wireless transceiver packaged in a single enclosure. Power is provided by an internal battery pack with disposable “C” cell (3.6V) batteries capable of continuous operation for greater than 60 days. An optional lithium ion rechargeable battery pack allows for five months of operation. Solar panels can provide charging of battery packs in safe areas. An optional battery pack with disposable “D” cell (3.6V) batteries is capable of delivering up to nine months of operation.



Reliable wireless technology

The proprietary “self-healing mesh” technology operates at 2.4 GHz and conforms to non licensed radio frequency appliance usage around the world. Wireless network integrity and security is accomplished using direct sequence spread spectrum DSSS programming topology. Wireless applications can be as simple as a single field device communicating with a host display or any number of field devices forming a network of subscribers. Each device in the network is assigned its unique device identification or a UID. Every device in the network can act as a router and repeater for all other devices in the network. This means that subscribers can “hop” through neighboring devices to communicate with each other thereby widening network access points. This unique and innovative technology is designed to create a robust network that automatically routes around congestion and line-of-sight obstacles while improving throughput as subscriber device density increases.

Features

- Self-healing mesh network topology
- Universally accepted 2.4 GHz non-licensed frequency
- Low power IR gas detection sensor with built-in transceivers
- Built-in display for gas sensor/field device HMI
- Disposable or rechargeable battery packs

Applications

- Oil and gas drilling rigs
- Work-over and pulling units
- Oil and gas production
- Turn-a-rounds in refining and petrochemical plants

Order guide

Part Number	Description
96C-IR0 _ 0 _ - 100	Model CXT-IR, 0-100 % LEL Combustible

To complete the part number please select from the options below. XXX - XXX _ X _ - XXX

Position "7" select SmartWireless Transceiver Option
 0 - CXT-DM with 300 fault tolerant transceiver
 2 - CXT-DM with 320 mesh transceiver

Position "9" Junction Box Selection & Power Selection
 1 - Aluminum Junction Box (no battery)
 2 - Stainless Steel Mini Junction Box, internal Battery Pack with Disposable "C" Cells (3.6V)
 3 - Stainless Steel Junction Box (no battery)
 4 - Aluminum Enclosure with Rechargeable Battery Pack
 7 - Aluminum Enclosure with High Output Rechargeable Battery Pack
 D - Aluminum Enclosure, internal Battery Pack with Disposable "D" Cells (3.6V)
 5 - None



3M™ Detcon™ CXT Wireless

Infrared LEL Gas Detection Sensor

System specifications

Sensor Type

Continuous diffusion/absorption
Non-dispersive Infrared Optical (NDIR) - combustible gas
sub-miniature plug-in field replaceable

Sensor Life

5 years typical

Measurement Range

0-100% Lower Explosive Limit (LEL)

Accuracy/Repeatability

±3% 0-50% LEL; ±5% 51-100% LEL

Response Time

T50 < 10 seconds, T90 < 30 seconds

Input/Output

2.4Ghz DSSS radio transmission

Safety Approvals

Explosion proof
cCSAus Class I, Division 1, Groups C, D (Tamb = 40° to + 60°C)
Class I, Zone 1, Group IIB
ATEX* Ex b ib IIB T4 Gb (Tamb = -40°C to + 60°C)
CE marking*
IECEx* Ex d ib IIB T4 Gb (Tamb = -40°C to + 60°C)

* "C" & "D" cell battery pack version only

Performance Approvals

cCSAus performance tested to ISA 12.13.01-2000 and CSA 22.2 #152

Ingress Protection

NEMA 4X

Warranty

Plug-in detector - 2 years
Transmitter - 2 Years

Mechanical specifications

Dimensions

With Stainless Steel Mini J-Box
18"H x 3.62"W x 4.3"D; 457mmH x 92mmW x 109mmD
18"H x 5.5"W x 4.3"D; 457mmH x 140mmW x 109mmD (with XP Power Switch)
20.5"H; 520mmH (with splashguard)
With Aluminum J-Box (rechargeable battery pack version)
19"H x 5.8"W x 8.5"D; 482mmH x 147mmW x 216mmD
19"H x 7.7"W x 8.5"D; 482mmH x 195mmW x 216mmD (with XP Power Switch)
21.5"H; 546mmH (with splashguard)

Weight

6 lbs/2.72 kg (w/stainless steel j-box)
5.2 lbs/2.36 kg (w/aluminum j-box)

AMERICAS

Texas (USA)

4055 Technology Forest
Blvd. The Woodlands,
TX 77381
Tel.: +1-713-559-9200
Fax: +1-713-893-6729

EMEA

ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX,
France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

ASIA PACIFIC

290 Guiqiao Road
Pudong,
Shanghai 201206
People's Republic
of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365

Battery specifications

Battery Pack with Disposable "C" Cells (3.6V):

Max. 2 months sensor run time full function
(-55°C to +85°C; -67°F to +185°F discharge temperature).

Battery Pack with Disposable "D" Cells (3.6V):

Max. 9 months sensor run time full function
(-55°C to +85°C; -67°F to +185°F discharge temperature).

Smart Lithium Ion Rechargeable Battery:

Max. 5 months sensor run time full function
(-20°C to +60°C; -4°F to +140°F discharge temperature;
-30°C intermittent).

Electrical specifications

Power Input

Internal battery pack with "C" size (3.6V) disposable batteries
Optional internal battery pack with "D" size (3.6V) disposable batteries
Optional Lithium Ion Rechargeable Battery Pack (CSA version only)

Power Consumption

25mW (typical), 420mW (max)

RF

Outdoor RF Line of Sight (with standard antenna): 1.5 miles
Interface Data Rate: 9,600bps
Throughput Data Rate: 19,200bps
RF Data Rate: 250,000bps
Transceiver Sensitivity: -102dBm
Frequency: 2.40-2.48GHz
RF Channels: 16, each 5Mz wide
Output Power: 100mW (20.5dBm) EIRP
Spread Spectrum: DSSS (Direct Sequence Spread Spectrum)
Modulation: 0-QPSK
Supported Network Topologies: Mesh, Point-to-Point

Antenna

5db Flex Whip; Screw on Radome Whip Antenna Guard Included
I/O Protection
Over-voltage, Miswiring, EMI/RFI Immunity

Environmental specifications

Operating Temperature Range

-40°F to +140°F; -40°C to +60°C

Storage Temperature Range

-40°F to +140°F; -40°C to +60°C

Operating Humidity Range

0-100% RH non-condensing

Accessory options

Tripod for mounting (specify pole mount and/or leg mount brackets)
Mini Tripod for mounting (specify pole mount and/or leg mount brackets)
7db gain antenna
Solar charging panel for battery charging in safe area only.

Refer to the CXT-300/320 data sheet for CXT-300/320 transceiver specific specifications
subject to change without notice

